

**EASYHEAT® Warm Tiles®
Electric Floor
Warming Cable Kit**

Warm Tiles



Place It!

Introducing the latest innovation in floor warming technology... DFT Cable Kits with longer lengths and metal strapping

Warm Tiles Cable Systems provide a quick and easy installation by utilizing two different cable spacing options. In a typical room above a heated area, simply space the cables 3" apart. For a room above an unheated area or a concrete slab, alternate the spacing from 3" (7.61 cm) to 1 1/2" (3.90 cm). Simply lace the cable into the metal strapping.

Lace It!

Set It!

EASYHEAT®
Warming Your World

www.warmtiles.com



*That's all there is to do.
We really do know how to make it **EASY!***



DFT Cable System

Free form cables are easy to adjust on site.

If the square footage of your heated area does not match a Warm Tiles Cable kit, you will need to adjust your walkable heated areas accordingly.

If total square footage is higher:
Reduce heated area.
If total square footage is lower:
Tighten cable spacing.

The Actual Coverage Chart provides you the exact square footage that each cable kit will cover. Heating Cables **CANNOT BE CUT** and must be embedded completely in mortar beneath the floor finish. Remember to follow the detailed instructions provided to you in each cable kit when installing your system.

Warm Tiles Cables

Easy Heat Item No.	Actual Coverage Area		Standard 3" Spacing	Alternating 3", 1.5" Spacing
	ft ²	(m ²)		
120 VOLT KITS				
DFT 1011	11	(0.98)	8	(0.74)
DFT 1016	16	(1.44)	12	(1.11)
DFT 1022	21	(2.00)	17	(1.58)
DFT 1030	30	(2.81)	23	(2.14)
DFT 1039	39	(3.60)	29	(2.69)
DFT 1048	48	(4.43)	37	(3.44)
DFT 1059	59	(5.46)	44	(4.09)
DFT 1069	69	(6.41)	51	(4.74)
DFT 1079	79	(7.34)	58	(5.39)
DFT 1088	88	(8.18)	64	(5.95)
DFT 1098	98	(9.10)	72	(6.69)
DFT 1108	108	(10.03)	80	(7.43)
240 VOLT KITS				
DFT 2021	21	(1.95)	15	(1.39)
DFT 2031	31	(2.88)	23	(2.13)
DFT 2053	53	(4.93)	38	(3.53)
DFT 2065	65	(6.04)	48	(4.46)
DFT 2078	78	(7.25)	57	(5.30)
DFT 2095	95	(8.83)	70	(6.50)
DFT 2118	118	(10.96)	87	(8.08)
DFT 2137	137	(12.73)	102	(9.48)
DFT 2157	157	(14.59)	116	(10.78)
DFT 2175	176	(16.35)	131	(12.17)
DFT 2195	196	(18.21)	145	(13.47)
DFT 2215	216	(20.07)	160	(14.86)

EASYHEAT
Warming Your World

www.warmtiles.com



For more information call:

Para obtener más información, llame al:

Pour plus d'information, veuillez appeler au:

US (800) 523-7636 • Canada (800) 794-3766

©2007 EASYHEAT, Inc. © EASYHEAT, Warm Tiles, One-Meter, Freeze Free, SFTrace, Deep Heat are Registered Trademarks of EASYHEAT, Inc.
40012-001 Rev 0

Advantages of the Floor Warming DFT Cable Kit

- Free form cable allows for full floor coverage by lacing the cables on the floor wherever you want a heated area
- Unlimited design configurations for even the most difficult shaped room
- Under 2 hours to install an average cable floor warming kit
- Energy and cost efficient, only 1¢ per day per square foot
- Only floor warming manufacturer to earn the Good Housekeeping Seal

* For use under engineered, floating wood floors only. Not approved for nail down installations.

**Interior use only.

† Consult cement backer board manufacturer for specific installation recommendations.

Cable Systems can be used over a variety of substrates (interior use only)

- Exterior Grade Plywood**
- Concrete/Masonry
- Cement Mortar Beds
- Existing Ceramic Tile
- Cement Backer Boards†
- Cement Terazzo
- Properly Prepared Vinyl
- Non-soluble cut-back adhesive

A wide variety of final floor finishes are ideal for use with Cable Systems

- Ceramic
- Porcelain
- Terrazzo
- Glass Mosaics
- Natural Stone
- Agglomerates
- Engineered Wood and Laminates*

Warm Tiles 120V Cable Kits

Model No.	Heated Area Standard FT ² (m ²)	Heated Area Alternating FT ² (m ²)	Ctn Qty	UPC Code
DFT 1011 BLUE	9-13 (0.84-1.21)	7-9 (0.65-0.84)	2	0-13627-01611-8
DFT 1016 RED	14-18 (1.30-1.67)	10-13 (0.93-1.21)	2	0-13627-01612-5
DFT 1022 GREEN	19-26 (1.77-2.42)	14-19 (1.30-1.77)	2	0-13627-01613-2
DFT 1030 YELLOW	27-34 (2.51-3.16)	20-26 (1.86-2.42)	2	0-13627-01614-9
DFT 1039 PURPLE	35-42 (3.25-3.90)	27-33 (2.51-3.07)	2	0-13627-01615-6
DFT 1048 ORANGE	43-54 (3.99-5.02)	34-39 (3.16-3.62)	2	0-13627-01615-6
DFT 1059 BROWN	55-65 (5.11-6.04)	40-48 (3.72-4.46)	2	0-13627-01617-0
DFT 1069 BEIGE	66-72 (6.13-6.69)	49-54 (4.55-5.02)	2	0-13627-01618-7
DFT 1079 WHITE	73-82 (6.78-7.62)	55-62 (5.11-5.76)	2	0-13627-01619-4
DFT 1088 PINK	83-92 (7.71-8.55)	63-69 (5.85-6.41)	2	0-13627-01609-5
DFT 1098 SILVER	93-102 (8.64-9.48)	70-76 (6.50-7.06)	2	0-13627-01608-8
DFT 1108 BLACK	103-113 (9.57-10.50)	77-85 (7.15-7.90)	2	0-13627-01607-1

Warm Tiles 240V Cable Kits

Model No.	Heated Area Standard FT ² (m ²)	Heated Area Alternating FT ² (m ²)	Ctn Qty	UPC Code
DFT 2021	18-25 (1.67-2.32)	13-19 (1.21-1.77)	2	0-13627-01621-7
DFT 2031	26-35 (2.42-3.25)	20-27 (1.86-2.51)	2	0-13627-01622-4
DFT 2053	48-55 (4.46-5.11)	35-44 (3.25-4.09)	2	0-13627-01623-1
DFT 2065	60-70 (5.57-6.50)	45-54 (4.18-5.02)	2	0-13627-01624-8
DFT 2078	71-83 (6.60-7.71)	55-63 (5.11-5.85)	2	0-13627-01625-5
DFT 2095	90-100 (8.36-9.29)	64-75 (5.95-6.97)	2	0-13627-01626-2
DFT 2118	110-130 (10.22-12.08)	84-94 (7.80-8.73)	2	0-13627-01627-9
DFT 2137	131-145 (12.17-13.47)	95-108 (8.83-10.03)	2	0-13627-01628-6
DFT 2157	146-165 (13.56-15.33)	109-125 (10.13-11.61)	1	0-13627-01629-3
DFT 2175	166-184 (15.42-17.09)	126-138 (11.71-12.82)	1	0-13627-01630-9
DFT 2195	185-204 (17.19-18.95)	139-153 (12.91-14.21)	1	0-13627-01631-6
DFT 2215	205-225 (19.50-20.90)	154-169 (14.31-15.70)	1	0-13627-01632-3

* **CAUTION:** Kit combinations that exceed 10 Amps should be connected by a qualified electrician.

Warm Tiles written instructions and warranty shall supercede information in this document. For the latest information, go to www.warmtiles.com.